

(FILE 'HOME' ENTERED AT 15:06:18 ON 07 OCT 1997)

FILE 'USPAT' ENTERED AT 15:06:25 ON 07 OCT 1997
L1 10062 S COHERENT(3A) (ILLUMINAT? OR LIGHT OR LASER OR SOURCE)
L2 63667 S SCATTER?
L3 2732 S L2 AND L1
L4 1230 S FRINGE(4A) (DETECT? OR SENS? OR MEASUR?)
L5 114 S L4 AND L3
L6 1780 S FRINGE#(4A) (DETECT? OR SENS? OR MEASUR?)
L7 181 S L3 AND L6
L8 93276 S (SURFACE OR PLATE OR SHEET OR AREA) (4A) (MOVEMENT OR MOTI
ON)
L9 13 S L8 AND L7

=> d 1-

1. 5,438,402, Aug. 1, 1995, System and method for measuring the interface tensile strength of planar interfaces; Vijay Gupta, 356/35.5, 32, 345, 353 [IMAGE AVAILABLE]
2. 5,426,498, Jun. 20, 1995, Method and apparatus for real-time speckle interferometry for strain or displacement of an object surface; Steven R. J. Brueck, et al., 356/35.5; 73/800; 356/357 [IMAGE AVAILABLE]
3. 5,357,341, Oct. 18, 1994, Method for evaluating interferograms and interferometer therefor; Michael Kuchel, et al., 356/353, 360 [IMAGE AVAILABLE]
4. 5,151,750, Sep. 29, 1992, Alignment apparatus; Nobutaka Magome, et al., 356/401; 257/797 [IMAGE AVAILABLE]
5. 4,884,283, Nov. 28, 1989, Ring laser gyroscope mirror orientation system and method; John Rahn, et al., 372/107; 356/350; 372/94 [IMAGE AVAILABLE]
6. 4,696,574, Sep. 29, 1987, Precision remote location of a movable point employing light interference fringes; Carl M. Penney, 356/375, 373; 901/47 [IMAGE AVAILABLE]
7. 4,591,996, May 27, 1986, Apparatus and method for determining stress and strain in pipes, pressure vessels, structural members and other deformable bodies; Reginald I. Vachon, 364/508; 73/800; 356/35.5, 360; 376/245, 248 [IMAGE AVAILABLE]
8. 4,470,696, Sep. 11, 1984, Laser doppler velocimeter; Paul T. Ballard, 356/28.5, 28 [IMAGE AVAILABLE]
- 9. 4,210,399, Jul. 1, 1980, System for relative motion detection between wave transmitter-receiver and irregular reflecting surface; Atul Jain, 356/28.5, 4.09; 367/89 [IMAGE AVAILABLE]
- 10. 4,113,388, Sep. 12, 1978, Optical apparatus for determining relative positioning of two members; John William Charles Gates, et al., 356/356; 250/237G; 356/354, 363 [IMAGE AVAILABLE]
11. 3,874,796, Apr. 1, 1975, Method of surface contouring; Joseph L. Chovan, et al., 356/359; 101/DIG.37; 250/550; 356/356, 390; 359/437, 561 [IMAGE AVAILABLE]

NOT AVAILABLE COPY

12. 3,870,414, Mar. 17, 1975, METHOD FOR SENSING SURFACE DISPLACEMENT
ORTHOGONAL TO THE DIRECTION OF OBSERVATION; Donald E. Coffey, 356/359;
73/655; 250/550; 356/356, 390; 359/559 [IMAGE AVAILABLE]

13. 3,572,882, Mar. 30, 1971, VARIABLE REFERENCE PHASE HOLOCAMERA TO
COMPENSATE FOR OBJECT MOTION; Don B. Neumann, 359/10; 250/201.9;
356/28.5, 347 [IMAGE AVAILABLE]

FILE 'USPAT' ENTERED AT 15:06:25 ON 07 OCT 1997

L1 10062 S COHERENT(3A) (ILLUMINAT? OR LIGHT OR LASER OR SOURCE)
L2 63667 S SCATTER?
L3 2732 S L2 AND L1
L4 1230 S FRINGE(4A) (DETECT? OR SENS? OR MEASUR?)
L5 114 S L4 AND L3
L6 1780 S FRINGE#(4A) (DETECT? OR SENS? OR MEASUR?)
L7 181 S L3 AND L6
L8 93276 S (SURFACE OR PLATE OR SHEET OR AREA) (4A) (MOVEMENT OR MOTI
ON)
L9 13 S L8 AND L7
L10 162 S L7 AND (POSITION SENS? OR DETECT?)
L11 41 S L7 AND (POSITION) (3A) (SENS? OR DETECT?)
L12 3 S L11 AND (BACKSCATTER? OR BACK SCATTER?)
L13 18 S L11 AND POLARIZ?
L14 11 S L10 AND L8
L15 4 S L11 AND L8

=> d 19 1-; d 112 1-; d 113 1-; d 1-

1. 5,438,402, Aug. 1, 1995, System and method for measuring the interface tensile strength of planar interfaces; Vijay Gupta, 356/35.5, 32, 345, 353 [IMAGE AVAILABLE]

2. 5,426,498, Jun. 20, 1995, Method and apparatus for real-time speckle interferometry for strain or displacement of an object surface; Steven R. J. Brueck, et al., 356/35.5; 73/800; 356/357 [IMAGE AVAILABLE]

3. 5,357,341, Oct. 18, 1994, Method for evaluating interferograms and interferometer therefor; Michael Kuchel, et al., 356/353, 360 [IMAGE AVAILABLE]

4. 5,151,750, Sep. 29, 1992, Alignment apparatus; Nobutaka Magome, et al., 356/401; 257/797 [IMAGE AVAILABLE]

5. 4,884,283, Nov. 28, 1989, Ring laser gyroscope mirror orientation system and method; John Rahn, et al., 372/107; 356/350; 372/94 [IMAGE AVAILABLE]

→ 6. 4,696,574, Sep. 29, 1987, Precision remote location of a movable point employing light interference fringes; Carl M. Penney, 356/375, 373; 901/47 [IMAGE AVAILABLE]

7. 4,591,996, May 27, 1986, Apparatus and method for determining stress and strain in pipes, pressure vessels, structural members and other deformable bodies; Reginald I. Vachon, 364/508; 73/800; 356/35.5, 360; 376/245, 248 [IMAGE AVAILABLE]

8. 4,470,696, Sep. 11, 1984, Laser doppler velocimeter; Paul T. Ballard, 356/28.5, 28 [IMAGE AVAILABLE]

9. 4,210,399, Jul. 1, 1980, System for relative motion detection between wave transmitter-receiver and irregular reflecting surface; Atul Jain, 356/28.5, 4.09; 367/89 [IMAGE AVAILABLE]

10. 4,113,388, Sep. 12, 1978, Optical apparatus for determining relative positioning of two members; John William Charles Gates, et al., 356/356; 250/237G; 356/354, 363 [IMAGE AVAILABLE]

11. 3,874,796, Apr. 1, 1975, Method of surface contouring; Joseph L. Chovan, et al., 356/3101/DIG.37; 250/550; 356/356, 357; 359/437, 561 [IMAGE AVAILABLE]

12. 3,870,414, Mar. 11, 1975, METHOD FOR SENSING SURFACE DISPLACEMENT ORTHOGONAL TO THE DIRECTION OF OBSERVATION; Donald E. Duffy, 356/359; 73/655; 250/550; 356/356, 390; 359/559 [IMAGE AVAILABLE]

13. 3,572,882, Mar. 30, 1971, VARIABLE REFERENCE PHASE HOLOCAMERA TO COMPENSATE FOR OBJECT MOTION; Don B. Neumann, 359/10; 250/201.9; 356/28.5, 347 [IMAGE AVAILABLE]

→ 1. 5,459,570, Oct. 17, 1995, Method and apparatus for performing optical measurements; Eric A. Swanson, et al., 356/345, 357, 360 [IMAGE AVAILABLE]

2. RE 34,121, Nov. 3, 1992, Method and system for correcting random walk errors induced by rate reversals in a dithered ring laser gyroscope; Rodney W. Benoist, 356/350; 372/94 [IMAGE AVAILABLE]

3. 4,844,615, Jul. 4, 1989, Method and system for correcting random walk errors induced by rate reversals in a dithered ring laser gyroscope; Rodney W. Benoist, 356/350 [IMAGE AVAILABLE]

1. 5,636,017, Jun. 3, 1997, Optical detection arrangement for small volume chemical analysis of fluid samples; Alfredo E. Bruno, et al., 356/246, 440 [IMAGE AVAILABLE]

2. 5,568,256, Oct. 22, 1996, Method and apparatus utilizing an optical stage for topographic surface analysis; Klaus Korner, et al., 356/359, 353, 354 [IMAGE AVAILABLE]

3. 5,528,390, Jun. 18, 1996, Exposure apparatus for reproducing a mask pattern onto a photo-sensitive surface of a substrate using holographic techniques; Akihiro Goto, et al., 359/12, 30, 35 [IMAGE AVAILABLE]

4. 5,506,684, Apr. 9, 1996, Projection scanning exposure apparatus with synchronous mask/wafer alignment system; Kazuya Ota, et al., 356/401; 250/548; 356/349, 363 [IMAGE AVAILABLE]

→ 5. 5,489,986, Feb. 6, 1996, **Position detecting** apparatus; Nobutaka Magome, et al., 356/401, 363 [IMAGE AVAILABLE]

6. 5,459,570, Oct. 17, 1995, Method and apparatus for performing optical measurements; Eric A. Swanson, et al., 356/345, 357, 360 [IMAGE AVAILABLE]

7. 5,432,605, Jul. 11, 1995, Interferometric cylinder sizing and velocimetry device; Amir A. Naqwi, et al., 356/357, 73.1, 345, 349 [IMAGE AVAILABLE]

8. 5,426,498, Jun. 20, 1995, Method and apparatus for real-time speckle interferometry for strain or displacement of an object surface; Steven R. J. Brueck, et al., 356/35.5; 73/800; 356/357 [IMAGE AVAILABLE]

9. 5,392,121, Feb. 21, 1995, Speckle interferometry spatial filters or the like to achieve using phase selection; Kotaro Hosaka, et al., 356/360, 351 [IMAGE AVAILABLE]

10. 5,341,205, Aug. 23, 1994, Method for characterization of optical waveguide devices using partial coherence interferometry; Matthew N.

McLandrich, et al., 356/73.1, 357, 358 [IMAGE AVAILABLE]

11. 5,272,501, Dec. 21, 1993, Projection exposure apparatus; Kenji Nishi, et al., 355/53, 43, 71; 356/401 [IMAGE AVAILABLE]

12. 5,227,862, Jul. 13, 1993, Projection exposure apparatus and projection exposure method; Yoshitada Oshida, et al., 356/363, 349, 351, 358 [IMAGE AVAILABLE]

13. 5,171,999, Dec. 15, 1992, Adjustable beam and interference fringe position; Koichiro Komatsu, et al., 250/548; 356/401 [IMAGE AVAILABLE]

14. 5,165,045, Nov. 17, 1992, Method and apparatus for measuring displacement having parallel grating lines perpendicular to a displacement direction for diffracting a light beam; Steven A. Eselun, 250/237G; 356/374 [IMAGE AVAILABLE]

15. 5,151,750, Sep. 29, 1992, Alignment apparatus; Nobutaka Magome, et al., 356/401; 257/797 [IMAGE AVAILABLE]

16. 4,952,058, Aug. 28, 1990, Method and apparatus for detecting abnormal patterns; Minoru Noguchi, et al., 356/237, 394, 446 [IMAGE AVAILABLE]

17. 4,929,077, May 29, 1990, Interferometric range finder; Andre Huisen, 356/4.09, 358 [IMAGE AVAILABLE]

18. 4,541,697, Sep. 17, 1985, Ophthalmic testing devices; Paul W. Remijan, 351/211, 205 [IMAGE AVAILABLE]

1. 5,426,498, Jun. 20, 1995, Method and apparatus for real-time speckle interferometry for strain or displacement of an object surface; Steven R. J. Brueck, et al., 356/35.5; 73/800; 356/357 [IMAGE AVAILABLE]

2. 5,151,750, Sep. 29, 1992, Alignment apparatus; Nobutaka Magome, et al., 356/401; 257/797 [IMAGE AVAILABLE]

3. 4,210,399, Jul. 1, 1980, System for relative motion detection between wave transmitter-receiver and irregular reflecting surface; Atul Jain, 356/28.5, 4.09; 367/89 [IMAGE AVAILABLE]

4. 4,113,388, Sep. 12, 1978, Optical apparatus for determining relative positioning of two members; John William Charles Gates, et al., 356/356;

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.